



DIN 7971

EN 21481
ISO 1481
PN 83106



Blachowkręt z łbem walcowym,
z nacięciem prostym

A2

dk	4,2	5,6	6,9	7,5	8,2	8,5	10,8	12,5
k	1,35	1,75	2,10	2,25	2,45	2,80	3,20	3,65
n	0,6	0,8	1,0	1,0	1,2	1,2	1,6	1,6
t	0,55	0,75	0,95	1,05	1,15	1,35	1,55	1,80

d	2,2	2,9	3,5	3,9	4,2	4,8	5,5	6,3
----------	-----	-----	-----	-----	-----	-----	-----	-----

l	4,5	1000						
	6,5	1000	1000	1000	1000			
	9,5	1000	1000	1000	1000	1000		
	13,0	1000	1000	1000	1000	1000	1000	500
	16,0	1000	1000	1000	1000	1000	1000	500
	19,0	1000	1000	1000	1000	1000	1000	500
	22,0	1000	1000	1000	1000	1000	1000	500
	25,0	1000	1000	1000	1000	1000	500	500
	32,0		1000	1000	500	500	500	500
	38,0		1000	500	500	500	500	200
	45,0				500	500	200	200
	50,0				200	200	200	200
	55,0							200
	60,0				200	200	200	200
	70,0					200	200	200

Ilość szt. w opakowaniu jednostkowym

ABAKOSTEEL Quality